2

RECEIVED
CENTRAL FAX CENTER
JUN 2 0 2007

Appl.No. 10/518,981 Amdt. Dated June 20, 2007 Reply to Office action of April 19, 2007

Amendments to the Claims

5

What is claimed is:

- 1. (Cancelled)
- 2.(Currently Amended) The tank according to claim 1 10, characterized in that the anti-overflow partition is fixed perpendicularly to the ceiling of the tank.
 - 3.(Cancelled)
 - 4.(Cancelled)
 - 5.(Cancelled)
- 15 6.(Cancelled)
 - 7.(Cancelled)
 - 8. (Currently Amended) The tank according to claim 7 10, characterized in that the second portion of the anti-overflow partition surrounding the periphery of the tank includes a series of corrugations (43).
 - 9. (Previously Amended) The tank according to claim 8, characterized in that each corrugation in the second portion of the anti-overflow partition is positioned in such a manner as to be placed in register with a stiffening rib (44).

25

30

35

20

- 10. (New) A hydraulic fluid tank (1) comprising:
 - a ceiling (2) and a bottom (3); and
- a hydraulic fluid feed orifice (11), said feed orifice is placed in the ceiling and opens out to the outside of the tank, the tank being characterized in that an anti-overflow partition (16) is placed inside the tank extending at least from the ceiling and surrounding the feed orifice at least in part, said tank characterized in that the anti-overflow partition is U-shaped and is fixed solely to the ceiling of the tank, said tank including a wall connecting the ceiling to the bottom, which wall is provided with stiffening ribs (44) that are preferably fixed perpendicularly thereto, said anti-overflow partition comprises a first portion (29) extending part of the way around the feed orifice, and a second portion (30) extending around a periphery (31) of the tank.